



Aero Still Chrome 125 ST


Extract fan for low-noise applications

- Maximum airflow: 158
- Sound pressure level LpA at 3 m: 31
- Motor type: AC
- Casing material: Plastic
- Backdraft protection: Backdraft damper
- Pull cord
- Timer: Turn off timer

| | Unit of measurement | Aero Still Chrome 125 ST |
|---------------------------------|---------------------|--------------------------|
| Connected air duct size | mm | 125 |
| Speed | - | 1 |
| Minimum supply voltage | V | 220 |
| Maximum supply voltage | V | 240 |
| Power supply frequency | Hz | 50 |
| Rated power | W | 9.4 |
| Unit current | A | 0.059 |
| Maximum airflow | m ³ /h | 158 |
| Sound pressure level LpA at 3 m | dB(A) | 31 |
| Ambient air temperature min | °C | 1 |
| Ambient air temperature max | °C | 40 |
| Ingress protection rating | - | IP34 |

Dimensions

| a | b | c | Ø d | e |
|-----|-----|----|-----|----|
| 168 | 144 | 97 | 125 | 30 |



Accessories

Other accessories

| Name | Photo | Description |
|--------------------------|--|----------------------------|
| CDT E1.8 |  | Thyristor speed controller |