



Axis-QR 350 4D

Wall-mounted axial fans

- Sound pressure level LpA at 3 m: 46
- Impeller type: Axial
- Casing material: Coated steel
- Installation in any position


	Unit of measurement	Axis-QR 350 4D	
Connected air duct size	mm	350	
Phases	-	3	
Minimum supply voltage	V	400	
Maximum supply voltage	V	400	
Power supply frequency	Hz	50	60
Rated power	W	140	
Unit current	A	0.38	
Maximum airflow	m³/h	2350	
Sound pressure level LpA at 3 m	dB(A)	46	
Weight	kg	7.5	
Transported air temperature (max)	°C	60	
Transported air temperature (min)	°C	-30	
Ingress protection rating	-	IP24	
Ingress protection rating of the drive	-	IP54	
Impeller material	-	Coated steel	






Dimensions

ØD	ØD1	ØD2	Ød	L
374	442	460	9	165


L
ø d
ø D1
ø D2


ø D+10
ø D

Ecodesign

Trademark	Blauberg
Model	Axis-QR 350 4D
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal external pressure (Pa)	80
Maximum external leakage rates (%)	2.7
Static efficiency (%)	31.7
Declared typology	NRVU UVU
Sound power level (dB(A))	82
Effective electric power input (kW)	0.129

Accessories

Thyristor speed controllers

Name	Photo	Description
CDT E1.8		Thyristor speed controller