



# Bravo Still Platinum 150 ST

Extract fans

- Maximum airflow: 235
- Sound pressure level LpA at 3 m: 35
- Motor type: AC
- Casing material: Plastic
- Backdraft protection: Backdraft damper
- Pull cord
- Timer: Turn off timer

|                                 | Unit of measurement | Bravo Still Platinum 150 ST |
|---------------------------------|---------------------|-----------------------------|
| Connected air duct size         | mm                  | 150                         |
| Speed                           | -                   | 1                           |
| Minimum supply voltage          | V                   | 220                         |
| Maximum supply voltage          | V                   | 240                         |
| Power supply frequency          | Hz                  | 50                          |
| Rated power                     | W                   | 20                          |
| Unit current                    | A                   | 0.13                        |
| Maximum airflow                 | m <sup>3</sup> /h   | 235                         |
| Sound pressure level LpA at 3 m | dB(A)               | 35                          |
| Ambient air temperature min     | °C                  | 1                           |
| Ambient air temperature max     | °C                  | 40                          |
| Ingress protection rating       | -                   | IP34                        |

## Dimensions

| a   | b   | c   | ∅ d | e  |
|-----|-----|-----|-----|----|
| 205 | 174 | 124 | 150 | 19 |



## Accessories

### Other accessories

| Name                     | Photo   | Description                |
|--------------------------|---|----------------------------|
| <a href="#">CDT E1.8</a> |  | Thyristor speed controller |