

# MERENFORT DTF 38L/350-ARI-2.0

Bidirectional flow central fresh air dehumidifier



- Maximum airflow: 350
- Extract filter: silver ions + G3
- Supply filter: silver ions + HEPA
- Sound insulation
- Motor type: DC
- Control: Wired control panel
- Humidity sensor
- CO2 sensor
- VOC sensor
- PM2.5 sensor
- Temperature sensor

|                                   | Unit of measurement | MERENFORT DTF 38L/350-ARI-2.0 |
|-----------------------------------|---------------------|-------------------------------|
| Connected air duct size           | mm                  | 150                           |
| Minimum supply voltage            | V                   | 220                           |
| Maximum supply voltage            | V                   | 220                           |
| Power supply frequency            | Hz                  | 50                            |
| Rated power                       | W                   | 390                           |
| Maximum airflow                   | m <sup>3</sup> /h   | 350                           |
| Sound pressure level LpA at 1,5 m | dB(A)               | 34                            |
| Heat recovery efficiency, max     | %                   | 60                            |
| Weight                            | kg                  | 92                            |
| Extract filter                    | -                   | silver ions + G3              |
| Supply filter                     | -                   | silver ions + HEPA            |
| Transported air temperature (max) | °C                  | 40                            |
| Transported air temperature (min) | °C                  | 1                             |

## Dimensions

