

Trio V2 100 TR


Low noise extract axial fan

- Sound pressure level LpA at 3 m: 28
- Casing material: Plastic
- Backdraft protection: Backdraft damper
- Timer: Turn off timer, Turn on timer

	Unit of measurement	Trio V2 100 TR	
Speed	-	1	2
Connected air duct size	mm	100	
Maximum supply voltage	V	240	
Minimum supply voltage	V	220	
Power supply frequency	Hz	50	
Rated power	W	5	8
Unit current	A	0.03	0.05
Maximum airflow	m^3/h	54	81
Sound pressure level LpA at 3 m	dB(A)	23	28
Weight	kg	0.55	
Ambient air temperature min	°C	1	
Ambient air temperature max	°C	40	
Ingress protection rating	-	IP44	
Impeller material	-	Plastic	

Dimensions

a	c	Ø d	e
150	79	99	23


□a
Ø d
c
e

Ecodesign

Trademark	Blauberg					
Model	Trio V2 100 TR					
Specific energy consumption (SEC) (kWh/(m²/a))	Cold		Average		Warm	
	-33.9	B	-16	E	-5.7	F
Type of ventilation unit	Unidirectional					
Type of drive installed	2-speed					
Type of heat recovery system	None					
Maximum flow rate (m³/h)	81					
Electric power input (W)	8					
Reference flow rate (m³/s)	0.015					
Specific power input (SPI) (W/(m³/h))	0.093					
Control typology	Clock control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	43					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	109		109		109	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	3667		1874		848	