



Turbo EC 125 eco T

Inline mixed-flow fans

- Sound pressure level LpA at 3 m: 28
- Impeller type: Mixed-flow
- Casing material: Plastic
- Installation in any position
- Timer: Turn off timer


	Unit of measurement	Turbo EC 125 eco T	
Connected air duct size	mm	125	
Phases	-	1	
Maximum supply voltage	V	230	
Minimum supply voltage	V	230	
Power supply frequency	Hz	50/60	
Rated power	W	10	16
Unit current	A	0.11	0.13
Maximum airflow	m³/h	228	275
Sound pressure level LpA at 3 m	dB(A)	26	28
Weight	kg	1.79	
Transported air temperature (max)	°C	40	
Transported air temperature (min)	°C	-25	
Ingress protection rating	-	IPX4	
Ingress protection rating of the drive	-	IPX4	
Impeller material	-	Plastic	


speed_1
speed_2
Static pressure [Pa]
150
125
100
75
50
25
0
0
25
50
75
100
125
150
175
200
225
250
275
Airflow [m3/h]



speed_1
speed_2
Power [W]
40
30
20
10
0
0
100
200
Airflow [m3/h]

Dimensions

∅ D	B	H	L
123	167	190	246



Ecodesign



Trademark	Blauberg					
Model	Turbo EC 125 eco T					
Specific energy consumption (SEC) (kWh/(m²/a))	Cold		Average		Warm	
	-49.3	A+	-24.3	C	-9.9	F
Type of ventilation unit	Unidirectional					
Type of drive installed	Variable speed					
Type of heat recovery system	None					
Maximum flow rate (m³/h)	280					
Electric power input (W)	37					
Reference flow rate (m³/s)	0.049					
Specific power input (SPI) (W/(m³/h))	0.135					
Control typology	Local demand control					
Maximum external leakage rates (%)	2.7					
Sound power level (dB(A))	57					
Declared typology	RVU UVU					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	78		78		78	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	5131		2623		1186	