



# Valeo-BPR 75/100 K TR

Mono-pipe ventilation exhaust centrifugal fans

- Maximum airflow: 100
- Sound pressure level LpA at 3 m: 38
- Control: Wired control panel
- Casing material: Plastic
- Backdraft protection: Backdraft damper
- Motion sensor
- Humidity sensor: Built-in
- Timer: Built-in

|                                 | Unit of measurement | Valeo-BPR 75/100 K TR |      |
|---------------------------------|---------------------|-----------------------|------|
| Connected air duct size         | mm                  | 80                    |      |
| Speed                           | -                   | 2                     |      |
| Minimum supply voltage          | V                   | 220                   |      |
| Maximum supply voltage          | V                   | 240                   |      |
| Power supply frequency          | Hz                  | 50                    |      |
| Rated power                     | W                   | 24                    | 29   |
| Unit current                    | A                   | 0.11                  | 0.13 |
| Maximum airflow                 | m <sup>3</sup> /h   | 75                    | 100  |
| Sound pressure level LpA at 3 m | dB(A)               | 29                    | 38   |
| Weight                          | kg                  | 2.7                   |      |
| Ambient air temperature min     | °C                  | 1                     |      |
| Ambient air temperature max     | °C                  | 40                    |      |
| Ingress protection rating       | -                   | IP55                  |      |

## Dimensions



## Accessories

### Other accessories

| Name                    | Photo  | Description        |
|-------------------------|--|--------------------|
| <a href="#">CDP-3/5</a> |  | Multi-speed switch |