

Hybrid Max

Decentralized unit for the small offices, facilities, classrooms and living spaces

- Heat exchanger type: Counter flow
- Heat exchanger material: Polystyrene, Enthalpy
- Sound-insulated casing
- Bypass: Auto
- BMS protocol: ModBus
- Casing material: Galvanized steel
- Humidity sensor: Optional
- CO2 sensor: Optional

Lineup	Maximum airflow, m³/h	Sound pressure level LpA at 3 m, dB(A)	Heat recovery efficiency, max, %	Reheater	Control	Mounting	Humidity sensor	CO2 sensor	VOC sensor
Hybrid Max S14	160	32	95	✕	Wireless control panel Smartphone Built-in control panel	Suspended	Optional	Optional	Optional
Hybrid Max S21	160	32	95	✕	Wireless control panel Smartphone Built-in control panel	Suspended	Optional	Optional	Optional
Hybrid Max E S21	160	32	95	Electric	Wireless control panel Smartphone Built-in control panel	Suspended	Optional	Optional	Optional
Hybrid Max E ERV S21	160	32	89	Electric	Wireless control panel Smartphone Built-in control panel	Suspended	Optional	Optional	Optional
Hybrid Max ERV S14	160	32	89	✕	Wireless control panel Smartphone Built-in control panel	Suspended	Optional	Optional	Optional

 Hybrid Max ERV S21	160	32	89	✖	Wireless control panel Smartphone Built-in control panel	Suspended	Optional	Optional	Optional
 Hybrid Max S21								Optional	Optional
 Hybrid Max S21								Optional	Optional
 Hybrid Max E S21								Optional	Optional