








Iso-Mix

Mixed-flow inline fans in sound-insulated casings















- Sound insulation
- Motor type: AC
- Impeller type: Mixed-flow
- Casing material: Coated steel
- Control: Built-in speed controller
- Timer: Turn off timer














Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m ³ /h	Cable with mains plug	Temperature sensor	Timer
 Iso-Mix 100	100	26	233	×	×	×
 Iso-Mix 125	125	29	347	×	×	×
 Iso-Mix 150	150	52	550	×	×	×
 Iso-Mix 160	160	52	550	×	×	×
 Iso-Mix 200	200	110	1035	×	×	×
 Iso-Mix 250	250	178	1315	×	×	×
 Iso-Mix 315	315	330	1920	×	×	×






 Iso-Mix 100 W1	100	26	233	✓	✗	✗
 Iso-Mix 100 US	100	26	233	✗	✗	✗
 Iso-Mix 100 T	100	26	233	✗	✗	✓
 Iso-Mix 100 FR1	100	26	233	✓	✗	✗
 Iso-Mix 100 USW1	100	26	233	✓	✗	✗
 Iso-Mix 100 TW1	100	26	233	✓	✗	✓
 Iso-Mix 100 TUSW1	100	26	233	✓	✗	✓
 Iso-Mix 100 TUS	100	26	233	✗	✗	✓
 Iso-Mix 100 GI1	100	26	233	✓	✓	✗
 Iso-Mix 100 G1	100	26	233	✓	✓	✗
 Iso-Mix 125 W1	125	29	347	✓	✗	✗
 Iso-Mix 125 US	125	29	347	✗	✗	✗
 Iso-Mix 125 T	125	29	347	✗	✗	✓

 Iso-Mix 125 FR1	125	29	347	✓	✗	✗
 Iso-Mix 125 USW1	125	29	347	✓	✗	✗
 Iso-Mix 125 TW1	125	29	347	✓	✗	✓
 Iso-Mix 125 TUSW1	125	29	347	✓	✗	✓
 Iso-Mix 125 TUS	125	29	347	✗	✗	✓
 Iso-Mix 125 GI1	125	29	347	✓	✓	✗
 Iso-Mix 125 G1	125	29	347	✓	✓	✗
 Iso-Mix 150 W1	150	52	550	✓	✗	✗
 Iso-Mix 150 US	150	52	550	✗	✗	✗
 Iso-Mix 150 T	150	52	550	✗	✗	✓
 Iso-Mix 150 FR1	150	52	550	✓	✗	✗
 Iso-Mix 150 USW1	150	52	550	✓	✗	✗
 Iso-Mix 150 TW1	150	52	550	✓	✗	✓

 Iso-Mix 150 TUSW1	150	52	550	✓	✗	✓
 Iso-Mix 150 TUS	150	52	550	✗	✗	✓
 Iso-Mix 150 GI1	150	52	550	✓	✓	✗
 Iso-Mix 150 G1	150	52	550	✓	✓	✗
 Iso-Mix 160 W1	160	52	550	✓	✗	✗
 Iso-Mix 160 US	160	52	550	✗	✗	✗
 Iso-Mix 160 T	160	52	550	✗	✗	✓
 Iso-Mix 160 FR1	160	52	550	✓	✗	✗
 Iso-Mix 160 USW1	160	52	550	✓	✗	✗
 Iso-Mix 160 TW1	160	52	550	✓	✗	✓
 Iso-Mix 160 TUSW1	160	52	550	✓	✗	✓
 Iso-Mix 160 TUS	160	52	550	✗	✗	✓
 Iso-Mix 160 GI1	160	52	550	✓	✓	✗

 Iso-Mix 160 G1	160	52	550	✓	✓	✗
 Iso-Mix 200 W1	200	110	1035	✓	✗	✗
 Iso-Mix 200 US	200	110	1035	✗	✗	✗
 Iso-Mix 200 T	200	110	1035	✗	✗	✓
 Iso-Mix 200 FR1	200	110	1035	✓	✗	✗
 Iso-Mix 200 USW1	200	110	1035	✓	✗	✗
 Iso-Mix 200 TW1	200	110	1035	✓	✗	✓
 Iso-Mix 200 TUSW1	200	110	1035	✓	✗	✓
 Iso-Mix 200 TUS	200	110	1035	✗	✗	✓
 Iso-Mix 200 GI1	200	110	1035	✓	✓	✗
 Iso-Mix 200 G1	200	110	1035	✓	✓	✗
 Iso-Mix 250 W1	250	178	1315	✓	✗	✗
 Iso-Mix 250 US	250	178	1315	✗	✗	✗

 Iso-Mix 250 T	250	178	1315	✗	✗	✓
 Iso-Mix 250 FR1	250	178	1315	✓	✗	✗
 Iso-Mix 250 USW1	250	178	1315	✓	✗	✗
 Iso-Mix 250 TW1	250	178	1315	✓	✗	✓
 Iso-Mix 250 TUSW1	250	178	1315	✓	✗	✓
 Iso-Mix 250 TUS	250	178	1315	✗	✗	✓
 Iso-Mix 250 GI1	250	178	1315	✓	✓	✗
 Iso-Mix 250 G1	250	178	1315	✓	✓	✗
 Iso-Mix 315 W1	315	330	1920	✓	✗	✗
 Iso-Mix 315 US	315	330	1920	✗	✗	✗
 Iso-Mix 315 T	315	330	1920	✗	✗	✓
 Iso-Mix 315 FR1	315	330	1920	✓	✗	✗
 Iso-Mix 315 USW1	315	330	1920	✓	✗	✗

 Iso-Mix 315 TW1	315	330	1920	✓	✗	✓
 Iso-Mix 315 TUSW1	315	330	1920	✓	✗	✓
 Iso-Mix 315 TUS	315	330	1920	✗	✗	✓
 Iso-Mix 315 GI1	315	330	1920	✓	✓	✗
 Iso-Mix 315 G1	315	330	1920	✓	✓	✗