











KOMFORT LE

Heat recovery air handling units

- Heat exchanger type: Cross flow
- Sound insulation
- Motor type: AC
- Reheater: Electric
- Control: Wired control panel
- Casing material: Galvanized steel

Lineup	Connected air duct size, mm	Speed	Phases	Maximum supply voltage, V	Rated power, W	Power of electrical reheater, W	Maximum airflow, m ³ /h	Sound pressure level LpA at 3 m, dB(A)	Heat exchanger material	Extract filter	Supply filter	Service side	Frost protection	Reheater
 KOMFORT LE 350-3	125	1	1	230	260	3000	350	24-45	Polystyrene	G4	G4	Right	Supply fan	Electric
 KOMFORT LE 500-3	150	1	1	230	300	3000	500	24-47	Polystyrene	G4	G4	Right	Supply fan	Electric
 KOMFORT LE 530-4	160	1	1	230	300	4000	530	28-47	Polystyrene	G4	G4	Right	Supply fan	Electric
 KOMFORT LE 600-4	200	1	1	230	390	4000	600	32-48	Polystyrene	G4	G4	Right	Supply fan	Electric
 KOMFORT LE 800-9	250	1	3	400	490	9000	800	48	Polystyrene	G4	G4	Right	Supply fan	Electric
 KOMFORT LE 1200-9	249	1	3	230	820	9000	1200	60	Polystyrene	G4	G4	Right	Supply fan	Electric
 KOMFORT LE 1700-18	315	1	3	230	980	18000	1750	49	Polystyrene	G4	G4	Right	Supply fan	Electric
 KOMFORT LE 2200-18	315	1	3	230	1300	18000	2200	65	Polystyrene	G4	G4	Right	Supply fan	Electric