

Trio

Low noise extract axial fan

- Casing material: Plastic
- Humidity sensor

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m³/h	Sound pressure level LpA at 3 m, dB(A)	Pull cord	Humidity sensor	Timer	Number of speeds
Trio 100	100	8	90	29	✗	✗	✗	1
Trio 100 S	100	8	90	29	✓	✗	✗	1
Trio 100 T	100	8	90	29	✗	✗	Turn off timer	1
Trio 100 TR	100	8	90	29	✗	✗	Turn off timer, Turn on timer	1
Trio 100 ST	100	8	90	29	✓	✗	Turn off timer	1
Trio 100 H	100	8	90	29	✗	✓	Turn off timer	1

 Trio 100 SH	100	8	90	29	✔	✔	Turn off timer	1
 Trio 150	150	28	255	35	✖	✖	✖	1
 Trio 150 S	150	28	255	35	✔	✖	✖	1
 Trio 150 T	150	28	255	35	✖	✖	Turn off timer	1
 Trio 150 TR	150	28	255	35	✖	✖	Turn off timer, Turn on timer	1
 Trio 150 ST	150	28	255	35	✔	✖	Turn off timer	1
 Trio 150 H	150	28	255	35	✖	✔	Turn off timer	1
 Trio 150 SH	150	28	255	35	✔	✔	Turn off timer	1
 Trio V2 100	100	8	81	28	✖	✖	✖	2
 Trio V2 100 TR	100	8	81	28	✖	✖	Turn off timer, Turn on timer	2
 Trio V2 100 H	100	8	81	28	✖	✔	Turn off timer, Turn on timer	2
 Trio V2 150	150	21	300	35	✖	✖	✖	2
 Trio V2 150 TR	150	21	300	35	✖	✖	Turn off timer, Turn on timer	2

 Trio V2 150 H	150	21	300	35	✗	✓	Turn off timer, Turn on timer	2